

Part Number: HD-FXD-6-DT-E, HD-FXD-FB-8-DT-E

Description: Heated Dual Touring Saddle

Fitment: 2006 Harley-Davidson Dyna-Glide

Revision: 1



Tools Required	Parts List
10mm socket or combination wrench Phillips head screwdriver	1 Wiring harness 1 Fuse adapter, small 3 Tie wraps (zip ties) 1 Heated Dual Saddle (of course)

1. Remove stock seat, battery cover and fusebox cover. You do not need to remove the battery.

2. Refer to Figure 1 for a look at a completed installation. Notice the pigtail harness wires directly to your bike and remains in place even with the saddle removed. You should leave about twelve inches of pigtail available to keep saddle installation easy.

3. Start by routing the pigtail under the chassis and along the top of your fender as shown in Figure 2. Route the red wire towards your fusebox and the black wire towards your battery.

4. Slip the battery out enough to give yourself access to the negative terminal and disconnect. You will be installing the black wire of the pigtail to this terminal later, but leave it out for now as a safety precaution. You should always disconnect the battery negative terminal when working on the electrical system of your bike. (Fig 3.)

5. Route the red (hot) wire through the back of the fuse box on your bike. Then attach the fuse adapter to the pigtail harness' positive wire (red).

6. Look for the **Accessories** fuse in the fusebox and remove it. Place this fuse in the empty slot of the fuse adapter as shown in Figure 4.

7. Slip the fuse adapter, with both fuses, into the **Accessories** slot of your fusebox in place of the fuse you just removed in step 6. Reinstall the fusebox cover.

Continued...



